

# DIGIPOS IT1500

## FACTS, FEATURES & SPECIFICATION

### The facts

**The DigiPoS Integrated Touch IT1500 is the new innovative semi-integrated touchscreen Point of Sale system with a stylish design – designed specifically for the retail, hospitality and leisure markets.**

It features advanced technology based on the similar ease and functionality of the DigiPoS Retail Blade™ technology. This systems outstanding reliability and simple design allow for secured, yet easy access to internal components. It utilises Intel processing power for high-performance demands and can endure the knocks and spills of harsh operating environments.

While conserving valuable counter space, the 15.1" TFT LCD Panel Display offers wide angle adjustment for true visibility. With the added option of the 10.4" LCD display retailers can enhance the customer experience – providing in-store advertisements and special offers.

Alternatively the Standard 2 line/20 character Rear Customer display is available.



### The features

- Advanced technology based on the similar ease of use and functionality DigiPoS Retail Blade™
- Easily accessible internal HDD/CD-ROM (No tools required)
- Two front accessible USB ports, two in rear
- Lockable front panel for security
- 15" Thin Bezel Resistive Touch Monitor
- 3 Year Warranty
- Intel processing power for high performance
- Small footprint, conserving valuable counter space

### The options

- Compact Flash option
- 10.4" LCD display gives retailers the opportunity to enhance the customer experience
- Standard 2 line/20 character Rear Customer display is also available
- Easily integrated with a Customer Display or Secondary LCD Display



PC-PoS UK Ltd: +44 (0)1256 390700

# DIGIPOS IT1500

## FACTS, FEATURES & SPECIFICATION

### The specification

<b>Mainboard CPU</b>	Celeron 2.0GHz (FSB400), Pentium M 1.6GHz (FSB533) or Pentium M 1.86GHz (FSB533)
<b>Display Model</b>	15" colour TFT, 1024 x 768, 250 nits
<b>Core Chipset</b>	Intel 852GM/ICH4
<b>Display</b>	4 X AGP LCD/VGA controller, advanced hardware 2D/3D GUI engine Sharing memory architecture up to 64MB
<b>System Memory</b>	1 x 184 pin supporting DDR up to 1GB
<b>L2 Cache</b>	CPU built-in
<b>Audio</b>	MIC-in, Speaker-out (front access)
<b>Speakers</b>	Internal speakers x 2
<b>Drive Bay</b>	1 x 3.5" HDD 1 x Slim CD-ROM or equivalent device 1 x Compact Flash slot (optional)
<b>Ethernet</b>	100/10 Base-T PnP Ethernet with RJ-45 phone jack Support Wake-on-LAN
<b>Panel PCI/O</b>	(Accessible inside Kiosk Cabinet) Serial Ports x 4, COM 1,2 & 4 with +5V/12V power output on pin 9, COM 3 is internal type reserved for touch screen, optional COM 5 1 x Parallel Port x 1: supports SPP/EPP/ECP PS/2 Mouse Interface 1 x PS/2 Keyboard Interface USB 2.0 x 4 (2 front & 2 rear access) 1 x VGA Interface Cash Drawer RJ-11 with 12V power output
<b>Power Supply</b>	ATX 120W, input range: 100~240V
<b>Touchscreen</b>	15.0" resistive type with RS-232 controller
<b>Dimensions</b>	379mm x 312mm x 358 mm (without second display) 379mm x 312mm x 408 mm (with second display)
<b>Peripheral Devices</b>	Slim type CD-ROM MSR: Magnetic card reader, swipe type, track I, II & III, KB wedge Customer Display (VFD): 20*2 lines RS-232 interface Customer Display (VFD) w pole: 20*2 lines RS-232 interface Second display: 10.4" LCD monitor Dallas i-Button w receptacle and magnetic key CF socket: CF function COM5: USB to COM5
<b>Stand</b>	Tilt angle: 15°~75° front/back, swivels left/right

**PC-PoS**  
UK

**PC-PoS UK Ltd**

Unit 4 Houndmills Industrial Estate  
Hamilton Close, Basingstoke  
Hampshire RG21 6YT

**Tel:** +44 (0)1256 390700

**Fax:** +44 (0)1256 356112

**Email:** sales@pc-pos.co.uk

**Website:** www.pc-pos.co.uk

PC-PoS UK Ltd: +44 (0)1256 390700