

DIGIPOS DIGITOUCH

FACTS, FEATURES & SPECIFICATION

The New all-in-one environmentally friendly Touch Solution from DigiPoS.

The facts

The Ultra Low Voltage design of the DigiPoS DigiTouch means reduced power consumption and energy-efficient operation - ideal for the environmentally aware business.

With a variety of peripheral devices to choose from such as magnetic strip reader, smart card reader, fingerprint recognition system, Dallas key, DigiPole display and secondary LCD display, the DigiTouch can be optimised to suit your needs.

The compact size increases counter space which together with a variety of peripheral options, delivers a fully flexible system suitable for Retail, Hospitality, Hotel, Supermarket, Casino, Theme Park etc.

The features

- Low-noise design suitable for noise-intolerant environments
- Ultra low voltage design delivers reduced power consumption
- Compact size increases counter space
- WEPOS / XPE Compliant
- RoHS compliant
- Cash drawer controller
- Powered USB outputs available
- Touch-screen

The options

- MSR, Pole Display, Smart Card Reader, Dallas Key, Fingerprint recognition system
- Secondary LCD Display
- Keyboard
- Programmable PoS Keyboard



DIGIPOS DIGITOUCH

FACTS, FEATURES & SPECIFICATION

The specification

CPU Support	DigiTouch ULV 1.0 Pro: VIA Eden 1 Ghz (fan-less), DigiTouch ULV 2.0 Pro: VIA Eden 2 Ghz (Low RPM fan)
System Core Logic	NB: VIA CN700 SB: VIA VT-8237R+
System RAM Module	DDR-200 Pin RAM socket x 1 (up to 1 GB)
Graphics	VIA S3 AGP up to 64MB
HDD	3.5" x 1
Compact Flash Card	Compact Flash Card Socket (Type I / II) x 1 Supported
LCD Size	15in TFT Panel with LVDS Interface
Touch Screen	15in LCD Touch Panel
Brightness	250 cd/m2
Resolution	1024 x 768 Max
Display Function	VIA Dual-view Built-in AGP 8X Shared Memory up to 64MB
Screen Adjustment	Brightness & Volume adjust button
Serial Port	6 total. 1 dedicated to Touch, 4 x conventional DB-9, 1 x RJ45 for Customer Display
USB Port	5 total 1 x 12V power USB, 1 x 24V power USB, 2 rear accessible, 1 front accessible
PS/2 Port	1 x combined keyboard & mouse port
LAN Port	Realtek RTL-8100CL Ethernet Port on board (10/100 Base-T)
Audio Port	Line Out
Cash Drawer Control Port	RJ12 Socket
DC Output for Peripherals	1 x 24V Hosidan connector, 1 x 12V barrel connector
Power Supply	DC 24V / 5A External Power Adapter (120W)
Safety	UL / CUL / FCC / CE / VCCI
Dimensions	380mm(L) x 280mm(W) x 360mm(H)
Operation Temperature	0-40 Degrees C
Options	
FDD	External USB FDD
CD-ROM	External USB CD-ROM / DVD ROM / COMBO
Programmable POS K/B	8 x 4 Matrix Programmable POS K/B with 6 stage Key Switch
Magnetic Stripe Reader	3 Track
Smart Card Reader	Smart Card Reader / Writer conforming to ISO 7816 Standard
Customer Display	2 x 20 VFD Customer Display
Secondary LCD Display	12.1in TFT LCD Display
Finger Print Sensor	Optical Finger Print Sensor
Security ID-Device	Dallas Key (I-Button)



PC-PoS UK Ltd
Unit 4 Houndmills Industrial Estate
Hamilton Close, Basingstoke
Hampshire RG21 6YT

Tel: +44 (0)1256 390700
Fax: +44 (0)1256 356112
Email: sales@pc-pos.co.uk
Website: www.pc-pos.co.uk

PC-PoS UK Ltd: +44 (0)1256 390700